

MODELO	612A
Ø VEIO SAÍDA	35 mm
RÁCIO APROXIMADO	60
RÁCIO EXATO	60.90
VELOCIDADE SAÍDA	24 RPM
VELOCIDADE SAÍDA EXATA	24 RPM
POTÊNCIA ENTRADA	0.75 KW
ROTAÇÃO ENTRADA	1400 RPM
PAM ENTRADA	80B5
TORQUE SAÍDA	299.08 N.m
TORQUE NOMINAL	400.00 N.m
POTÊNCIA NOMINAL	1 KW
FATOR SERVIÇO	1.33
EFICIÊNCIA DINÂMICA	0.96

QUANTIDADE DE ÓLEO (L)

B3/H1	B6/H4	B7/H3	B8/H2	V5/H5	V6/H6
0.8	1	1.2	1.2	1.3	1.35

CARGAS RADIAIS E AXIAIS



n_2 [min-1]	F_A [N]	F_R [N]
300	560	2800
200	640	3200
120	760	3800
15	1300	6500

Universal Motors S.A.
Rua Comendador Brandão, 484
4495-375 Póvoa de Varzim
geral@universalmotors.pt
TEL.: 252 299 080

Universal Motors UK, Ltd
Unit E2, Meltham Mills Road
West Yorkshire HD9 4AR
enquiries@universalmotors-group.co.uk
TEL.: +44(0) 1484660222

Universal Motors SL
C/La Habana n.6 nave 4 PI Camporoso
28806 Alcala de Henares
info@universalmotors-group.es
TEL.: 918 864 213

Gearbox weight peso riduttore	With flange	14.1 kg
	With feet	14.5 kg



Feet Code	Market reference	G	H	R	L	S	H1	O	Øl	S2 only with motor flange	B5 max. Flange	kit code
B4	412/3	20	130	180	149.5	216	242	18	14	-	-	KC60.9.024
S4	47-57	30	115	135	165	170	227	25	14	13 132B5	-	KC50.9.022
M3	62/3	35	120	170+185	110	230	232	20	14	8 132B5	-	KC60.9.023
S7	77	35	140	170	205	204	252	8	14	-	-	KC60.9.029LM
H4	024-243	35	155	170	150	225	267	30	14	-	-	KC60.9.025

 Most popular types
Tipi più diffusi

Technical drawing of the KC50.9.011 motor showing front, side, and detail views with dimensions.

Front View Dimensions:

- Overall width: 8.5 with KC50.9.011
- Mounting flange diameter: $\varnothing 2.5$
- Mounting flange thickness: 2.5
- Motor body diameter: $\varnothing d1$
- Motor body height: $h1$
- Output shaft diameter: $\varnothing p1$
- Output shaft length: x

Side View Dimensions:

- Overall height: 96
- Mounting flange thickness: 16.3
- Motor body height: $a1$
- Motor body diameter: $b1 \pm 0.7$
- Output shaft diameter: $\varnothing f1$
- Output shaft length: $c1$
- Output shaft offset: 67.5
- Overall width: 61.5 with KC50.9.011

Detail Y: A circular detail showing the mounting flange and motor body connection.

***Available output shaft / Albero di uscita**

***Available output shaft** / Albero di uscita

	Shaft - d1	p1	h1	x
Standard	ø 35x70	10	38	M10x22
On request A richiesta	ø 28x60	8	31	M8x20
	ø 30x60	8	33	M10x22
	ø 38x70	10	41	M10x25
	ø 40x80	12	43	M12x28

Available output flanges / flange di uscita

a1 Ø	b1	c1	e1	f1	s1	kit code
160	110	14	130	3.5	11	KC50.9.011
200	130	13	164	3.5	11	KC50.9.012
250	180	15.5	215	4	14	KC50.9.013

With flange and feet only on request. Ask for compatibility

With flange and feet
only on request.
Ask for compatibility

Technical drawing of the B14 motor flange assembly, showing side and top views with dimensions.

Side View Dimensions:

- Total length: 219
- Mounting flange thickness: 96
- Central shaft diameter: $\varnothing 35$ h6
- Mounting flange diameter: 181.5
- Motor flange diameter: 123
- Motor flange thickness: 12.5
- Motor flange width: 70
- Motor flange height: 16.3
- Motor flange width: 60
- Motor flange height: 15.5
- Motor flange width: 5
- Motor flange height: 10
- Motor flange width: 38
- Motor flange height: 10

Top View Dimensions:

- Mounting flange diameter: 181.5
- Motor flange diameter: 123
- Motor flange thickness: 12.5
- Motor flange width: 70
- Motor flange height: 16.3
- Motor flange width: 60
- Motor flange height: 15.5
- Motor flange width: 5
- Motor flange height: 10
- Motor flange width: 38
- Motor flange height: 10


Angles:

- 65° (Mounting flange angle)
- 50° (Motor flange angle)

Labels:

- Suggested B14 motor flanges
- N.5 M10x17
- M10x22

R612A-N... Input Shaft
Albero in entrata



B5 Motor Flanges	A	C_{max}	g6	k1	kit code	k1 with KC50.9.011	B14 Motor Flanges	A	C_{max}	g6	k1	kit code	k1 with KC50.9.011
71 B5	237.5	251.3	160	240	K023.4.041	246	80 B14	239.5	231.3	120	242	K085.4.046	248
80/90 B5	239.5	271.3	200	242	K023.4.042	248	90 B14	239.5	241.3	140	242	K085.4.045	248
100/112 B5	248.5	296.3	250	251	K023.4.043	257	100/112 B14	248.5	251.3	160	251	K085.4.047	257
132 B5	269.5	321.3	300	269	KC51.4.043	275	132 B14	269.5	271.3	200	269	KC51.4.041	275